LF16 Water Pressure Switch

LF16 Water pressure switch provide time tested, reliable control for automatic water supply systems. The switch is universally acceptable for use as original equipment on water pumps or pumping systems.



Specification

Model	Min On (Cut-In) PSI	Max Off (Cut-Out) PSI	Differential PSI	Factory Setting PSI	Electrical Rating			Contact	
					1 Phase		3 Phase	Arrange-	
					120VAC	240VAC	240VAC	ment	
LF16	20	80	15-30	20-40	2HP	3НР	5HP	NC	1/4Male or Female NPT
			15-30	30-50	2HP	3НР	5HP	NC	1/4Male or Female NPT
			15-35	40-60	2HP	3HP	5HP	NC	1/4Male or Female NPT
LF16-1	20	80	15-30	20-40	1.5HP	2HP	3HP	NC	1/4Male or Female NPT
			15-30	30-50	1.5HP	2HP	3НР	NC	1/4Male or Female NPT
			15-35	40-60	1.5HP	2HP	3HP	NC	1/4Male or Female NPT

Conversion: 1Kgf/cm² = 14.2PSI 1Bar = 14.5PSI Other connections are available on request.





尺寸单位: mm (Dimension in mm)

LF16 Order Ref. No.

i.e.: LF16(-1)-111-30PSI-50PSI

Pressure setting:Cut in:30PSI Cut off:50PSI

→ Connection Size:1/4NPT

→ Connection Type:SinglePort,Female

Number	Connect	ionType	Connection Size		
1	Single port	Female	1/4NPT		
2	1	Male	3/8NPT		
3	1	1	R1/4		
4	1	/	R3/8		
5	/	/	G1/4		
6	/	/	G3/8		

